

(12) NACH DEM VERTRAG ÜBER DIE INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES
 PATENTWESENS (PCT) VERÖFFENTLICHTE INTERNATIONALE ANMELDUNG

(19) Weltorganisation für geistiges Eigentum
 Internationales Büro



(43) Internationales Veröffentlichungsdatum
 29. April 2004 (29.04.2004)

PCT


(10) Internationale Veröffentlichungsnummer
 WO 2004/035995 A1

- (51) Internationale Patentklassifikation⁷: F01L 1/352, F16H 35/00, 25/06
- (21) Internationales Aktenzeichen: PCT/EP2003/011004
- (22) Internationales Anmeldedatum:
 4. Oktober 2003 (04.10.2003)
- (25) Einreichungssprache: Deutsch
- (26) Veröffentlichungssprache: Deutsch
- (30) Angaben zur Priorität:
 102 47 204.1 10. Oktober 2002 (10.10.2002) DE
- (71) Anmelder (für alle Bestimmungsstaaten mit Ausnahme von US): INA-SCHAEFFLER KG [DE/DE]; Industriestrasse 1-3, 91074 Herzogenaurach (DE).
- (72) Erfinder; und
- (75) Erfinder/Anmelder (nur für US): KLINDWORTH, Jan [DE/DE]; Seestr. 3b, 82418 Murnau (DE).
- (74) Gemeinsamer Vertreter: INA-SCHAEFFLER KG; Industriestrasse 1-3, 91074 Herzogenaurach (DE).
- (81) Bestimmungsstaaten (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,

[Fortsetzung auf der nächsten Seite]

(54) Title: ADJUSTING DEVICE

(54) Bezeichnung: VERSTELLVORRICHTUNG



(57) Abstract: The invention relates to an adjusting device for adjusting two parts (2, 3) with regard to one another that is used as a camshaft adjuster. The aim of the invention is, with an easy and smooth operability, to ensure a self-locking and an at least extensive play-free, continuous adjustment of the two parts with a high level of efficiency. To this end, the adjusting device comprises a first part (2) with webs (2.3, 22.3), which are interspaced in the peripheral direction and between which chambers (2.4) are formed, and comprises a second part (3) with an internal gearing (3.2, 13.2), and a number of teeth (7, 27) that are arranged inside the chambers (2.4) while being interspaced in the peripheral direction. The adjusting device also comprises an inner contact surface (7.4) for resting against an eccentric drive element (6), and comprises an outer contact surface (7.5) for engaging inside the internal gearing (3.2, 13.2). When an input shaft (4) is rotated by the teeth (7, 27) located inside the chambers (2.4), rotational motions about rotation axes, which are parallel to rotation axis (A) of the parts (2, 3), can be executed.

(57) Zusammenfassung: Die Erfindung betrifft eine Verstellvorrichtung zum Verstellen zweier Bauteile (2, 3) relativ zueinander, die als Nockenwellenverstellung verwendet wird. Um bei einfacher und leichtgängiger Bedienbarkeit eine Selbsthemmung und zumindest weitgehend spielfreie, stufenlose Verstellung der zwei Bauteile mit hohem Wirkungsgrad zu gewährleisten, weist die Verstellvorrichtung aufein erstes Bauteil (2) mit in Umfangsrichtung beabstandeten Stegen (2.3, 22.3), zwischen denen Kammern (2.4) ausgebildet sind, ein zweites Bauteil (3) mit einer Innenverzahnung

[Fortsetzung auf der nächsten Seite]



KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

PT, RO, SE, SI, SK, TR), OAPI-Patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Veröffentlicht:

— mit internationalem Recherchenbericht

(84) **Bestimmungsstaaten (regional):** ARIPO-Patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), eurasisches Patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), europäisches Patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL,

Zur Erklärung der Zweibuchstaben-Codes und der anderen Abkürzungen wird auf die Erklärungen ("Guidance Notes on Codes and Abbreviations") am Anfang jeder regulären Ausgabe der PCT-Gazette verwiesen.

(3.2, 13.2), undmehrere Zähne (7, 27), die in Umfangsrichtung zueinander beabstandet in den Kammern (2.4) angeordnet sind, jeweils eine innere Anlagefläche (7.4) zur Anlage an einem exzentrischen Antriebsglied (6) und eine äußere Anlagefläche (7.5) zum Eingriff in die Innenverzahnung (3.2, 13.2) aufweisen, wobei bei Drehung einer Eingangswelle (4) von den Zähnen (7, 27) in den Kammern (2.4) Drehbewegungen um zu der Drehachse (A) der Bauteile (2, 3) parallele Drehachsen durchführbar sind.

Translation of PCT/EP2003/011004

ADJUSTING DEVICE

5

Description

Field of the invention

The invention relates to an adjusting device for adjusting a camshaft relative to
10 a camshaft gear wheel driven by a crankshaft, wherein parts provided for the
adjustment procedure are arranged on the camshaft gear wheel and on the
camshaft, according to the preamble of Claim 1.

Among other things, stepper motors, which enable self-locking and an exact,
15 but merely discrete, i.e., non-continuous, adjustment, can be used as adjusting
devices. Furthermore, for achieving self-locking and a high gear reduction, a
worm gear pair can be used. However, for a relatively large amount of friction,
worm gear pairs exhibit low efficiency and require materials that are resistant
to wear and heat.

20

DE 195 08 328 A1 presents a self-locking adjusting device for rotating two
bracing parts relative to each other. One of the two bracing parts comprises
internal gearing, into which locking bars or teeth can be inserted in a straight-
line radial direction. The teeth are guided in chambers between webs of the
25 other bracing part, such that the radially inwards and outwards movement is
precisely enabled. The teeth are supported inwards on a control surface, which
is formed as an outer surface of an egg-shaped control element. When the
control element rotates, the teeth are thus periodically pushed outwards in the
radial direction, wherein a few of the teeth engage in the teeth gaps. The outer

end sections of the teeth and the recesses or teeth gaps of the internal gearing taper outwards, so that the teeth transfer torque between the webs of the second bracing part and the internal gearing of the first bracing part for eccentric insertion into a recess.

5

However, a disadvantage in this adjusting device is first that only partial self-locking is achieved. When torque acts upon the bracing part with internal gearing, only the one or two teeth, which are pressed against the eccentric region of the control element by the teeth of the internal gearing, contribute to the self-locking effect, depending on the engagement situation of the teeth. The
10 opposing teeth likewise contribute minimally to the self-locking, like those teeth, which are in the radially outer position, i.e., positive-fit in the recess, and those teeth, which are in the radially inner position, i.e., not engaged in the teeth gaps of the internal gearing. However, the possibly only one tooth, which
15 is to contribute to the self-locking effect, can transfer a force not directed towards the rotational axis from the internal gearing to the control element between the point of application of the internal gearing at its outer contact surface and its inner contact surface contacting the control element, which thus leads to transmission of torque. In this way, especially for the use of only a few
20 teeth, no positive-fit connection between the internal gearing and the webs and thus, at least for an unfavorable engagement situation of the teeth, also no complete self-locking can be achieved.

Furthermore, a play-free configuration of such an adjusting device is problem-
25 atic. The teeth that can move linearly in the radial direction slide with their side surfaces on the side surfaces of the webs of the second bracing part. However, a play-free arrangement of the teeth between the webs is practically impossi-

ble; for achieving a low-friction guidance of the teeth between the webs, a certain overdimension is necessary. Finally, due to the manufacturing-specific tolerances, play between the control surface and the tooth remains even in the positive-fit engagement of a tooth in its radially outer position in a recess of the
5 internal gearing.

Camshaft adjusters are used especially for engine speed-dependent and load-dependent adaptation of the valve opening and closing times for an internal-combustion engine in order to improve the filling. The camshaft is driven by
10 the crankshaft, e.g., by means of toothed belts, a roller chain, or spur pinions, on a camshaft gear wheel, to which the camshaft is connected. The camshaft adjustment is realized by rotating the camshaft relative to the camshaft gear wheel, wherein the transfer of torque must also be guaranteed during the adjustment. Therefore, adjusting devices with high, continuous adjustment
15 accuracy and reliable self-locking are required in all situations. For this purpose, in conventional camshaft adjusting devices, a control piston adjusts against a spring force in a flanged shaft connected to the camshaft through, e.g., a hydraulic drive, wherein the flanged shafts are connected to the camshaft gear wheel and, if necessary a positioning piston, by means of oblique gearing.
20 However, such a configuration is complicated, expensive, and subject to maintenance. Furthermore, complicated feed lines from a central hydraulic pump are required in the vehicle.

The invention is based on the objective of providing an adjusting device, which
25 ensures self-locking and at least essentially play-free, continuous adjustment of two parts for simple and smooth-running operability. Advantageously, a high gear reduction should be achievable.

This objective is met by the features of Claim 1. The subordinate claims describe preferred improvements.

5 According to the invention, the teeth thus execute rotational movements during the adjusting movement. These movements of the teeth in general can be superimposed movements of a linear movement directed outwardly and inwardly in the radial direction and a rotational movement of the teeth about a rotational axis parallel to the rotational axis of the parts. In an especially
10 preferred way, the teeth each run on a circular arc path from their inner contact with the drive element to the outer contact with the internal gearing and back on another circular arc path.

The rotational movements of the teeth according to the invention permits a
15 good adaptation of the shape of the teeth and webs, as well as the internal gearing, to the course of movement, which enables a self-locking engagement of a part of the teeth. In this way, in particular, a more favorable transfer angle between the moving tooth and the internal gearing is achieved, in which the force transfer from the moving tooth to the internal gearing is realized with a
20 small radial part, so that a higher efficiency can be achieved. Furthermore, in particular a defined contact of a tooth to the two adjacent webs is enabled, which leads to a reduction of the play.

Advantageously, in this way, in the outermost radial position of a tooth, there is
25 no contact with the internal gearing in order to guarantee a defined contact with the adjacent webs also in the position. The coupling of the teeth to the internal

gearing is thus realized at the preferably oblique tooth faces, wherein at least one tooth contacts a front or back tooth face in the rotational direction.

An eccentric is preferably provided as a drive element for adjusting the teeth.

5 For this purpose, an eccentrically mounted circular disk is mounted directly on the input shaft. The teeth contact the outer surface of this circular disk with their inner contact surfaces. However, advantageously as an extension, an eccentric ring is provided between the eccentric disk and the inner contact surfaces of the teeth. Here, the eccentric ring essentially executes a wobble
10 movement without rotation, so that a drive of the teeth is enabled without a frictional connection of their inner contact surfaces to the eccentric ring. The teeth merely roll with slight roller friction on the eccentric ring, so that a higher efficiency is achieved.

15 To achieve a defined contact of the teeth to the drive element, these are advantageously biased in the radial direction. This can be realized in one method through biasing towards the rotational axis, which, e.g., is exerted by a biased elastic O-ring, e.g., a rubber ring. Here, the O-ring can surround axial projections or regions of the teeth, wherein it can also be set, e.g., through
20 recesses of the teeth. Furthermore, biasing can be realized outwardly. This biasing can be realized, e.g., through a biased spring element, which sits on the shaft and presses the eccentric disk in a direction radially outwardly. Here, the spring element can be deformed purely elastically or mounted in the adjusting device under partial plastic deformation. Furthermore, radial biasing outwards
25 is also possible, e.g., through an overdimension. However, in principle biasing is not required.

The rotational movement of the teeth can be initiated advantageously by a control surface at their radially inner reverse point acting as the bottom dead center. The control surface comes into contact with the inner contact surfaces of the teeth, when these are in their radially inner positions. In this way, in particular, a jamming effect of the teeth in the bottom dead center of their movement can be avoided. The control surface can be especially a control gearing region of a control gear wheel rotationally fixed to the second part or embodied integrally with this part. In particular, external gearing can be used as the control gearing. Here, the inner contact surface of a tooth comes into engagement with tooth gaps or recesses of the external gearing of the second part. Instead of external gearing, internal gearing can also be provided accordingly.

The tooth can, according to one embodiment, be turned about a rotational point defined on the first part, in that a tab of the tooth engages in a corresponding guide in the chamber between the webs of the other part. The guide tapers inwards in the radial direction in order to guarantee the defined rotational point at the radially inner position of the tooth and to enable both the inwardly directed, and also the outwardly directed circular arc path at the radially outer positions, in which the side surfaces of the teeth slide in a defined way on the side surfaces of the webs.

Alternatively, the teeth and webs can also have shoulder regions, which ensure the defined rotational movement for the sliding movement of the teeth on the webs.

Furthermore, here a control disk with a control surface creating a frictional connection with the inner contact surfaces of the teeth can also be provided, which is fixed, e.g., rotationally, to the input shaft or to the drive element.

5 The adjusting device according to the invention is robust and can transfer high torque forces with reliable self-locking and can guarantee precise position adjustment. Through the favorable transfer angle between the moved tooth and the internal gearing, a high efficiency can be achieved. Advantageously, a high gear reduction is achieved, so that the use of fast-running, small-sized, and
10 cost-effective motors with small output torque is possible.

The adjusting device according to the invention is formed as a camshaft adjusting device, which adjusts the camshaft relative to a camshaft gear wheel driven by the crankshaft. Here, an activation of the input shaft is required only
15 for the adjustment process; no activation or power is required in the corresponding positions due to the self-locking.

The invention is explained in more detail in the following with reference to the attached drawings using a few exemplary embodiments. Shown are:

20

Figure 1 an exploded view of an adjusting device according to an embodiment of the invention;

Figure 2 a cross section of the adjusting device according to Figure 1;

25

Figure 3 a longitudinal section of the adjusting device according to Figure 1;

Figure 4 a perspective view of the assembled adjusting device;

Figures 5a, b a front view and side view of a tooth according to the
5 invention used in the adjusting device;

Figure 6 a cross section with illustration especially of the teeth engaging in
the internal gearing;

10 Figure 7 a cross section or superimposed view, especially of the teeth
engaging in the external gearing;

Figures 8a-d the representation of the movement of a tooth between
adjacent webs;
15

Figures 9a-d the representation of the movement of a tooth between the
internal and external gearing;

Figures 10a-c front, side, and rear views of the second part;
20

Figures 11a-c front, side, and rear views of the first part;

Figure 12 disassembled representation of the device for adjusting a cam-
shaft;
25

Figure 13 a cross section of an adjusting device according to another
embodiment of the invention.

According to Figure 1, as a first part an adjusting device 1 has a first flange part 2, which can be connected to a camshaft via attachment holes 2.1. The first flange part 2 has a center hole 2.2 and webs 2.3, which are spaced apart from each other in the peripheral direction, which project in the axial direction, and between which chambers 2.4 are defined. A second flange part 3 acting as a second part has attachment holes 3.1 for mounting on a camshaft wheel and internal gearing 3.2 with teeth 3.3 and recesses 3.4 formed between the teeth 3.3. An input shaft 4 has a square region 4.1, in which, on two opposing sides, spacing holders 4.4 are set and on another side an elastic (possibly also with additional plastic biasing), tensioned biasing spring element 4.3 is set. A circular disk 4.2 with square center hole 4.5 is set on the spacing holders 4.4 and the biasing spring element 4.3. The disk 4.2 is pressed radially outwards by the biasing spring element 4.3 and is used in its eccentric position as an eccentric disk 4.2. The spacing holders 4.4 glide on the square region 4.1 and/or on the eccentric disk 4.2.

An eccentric ring 6 is set around the eccentric disk 4.2 and executes a wobble movement when the input shaft 4 rotates. Teeth 7 are distributed in the peripheral direction such that with their inner contact surfaces 7.4 they contact the eccentric ring 6 and extend away from the rotational axis A. Outer contact surfaces 7.5 of the teeth 7 engage in the internal gearing 3.2 of the second part 3 when the input shaft 4 rotates. Through the biasing of the biasing spring element 4.3, the teeth 7 are pressed into the internal gearing 3.2. An O-ring 8 is set with biasing around axially extending projections 7.1 of the teeth 7 and creates a contact between each tooth 7 with its inner contact surface 7.4 and the outer side of the eccentric ring 6. In principle, the biasing by the O-ring 8 or by

the biasing spring element 4.3 (and the projections 7.1) can be eliminated, because one of the two biasing means is sufficient. A biasing ring 10 is used for pressing the parts in the axial direction.

5 The guidance of the teeth 7 in the chambers 2.4 between the webs 2.3 can be seen especially in Figure 2 and Figures 8 and 9, because the teeth 7 are in various successive engagement positions for the rotating eccentric disk 4.2. The lowermost tooth 7 in Figure 2 is in the innermost position in the radial direction, at which it contacts the apex point of a tooth 3.3 of the internal
10 gearing 3.2 with its outer contact surface 7.5. Here, the tooth 7 extends precisely in the radial direction. The uppermost tooth 7 in Figure 2 is in its outermost position in the radial direction, at which it is in engagement with a recess 3.4 (tooth gap) of the internal gearing 3.2. Torque is applied to this tooth
15 7, as well as the other teeth approximately in the bottom half shown in Figure 7, through the external gearing 5.2, which creates a defined tipping of the tooth in the innermost position acting as the bottom dead center of the inwards and outwards movement of the teeth. Between the innermost and outermost positions, the teeth 7 move on circular arc paths. The teeth 7 taper according to Figure 5 from the inner contact surface 7.4 to the outer contact surface 7.5,
20 which can be embodied flat or also curved as shown. Side surfaces 7.6 of the teeth advantageously have concave side surface regions 7.7. The teeth 7 glide according to Figure 8 with their side surfaces 7.6 essentially with the concave side surface region 7.7 on the webs 2.3. The webs 2.3 taper towards the rotational axis A, are formed essentially with a triangular or wedge shape, and
25 likewise advantageously have concave side surface regions 2.6.

In the chambers 2.4, additional guides 2.7 are formed as recesses, in which axially projecting tabs 7.9 of the teeth 17 engage. The tabs 7.9 are arranged approximately in the center of the teeth 7 and extend in the axial direction opposite to the projections 7.1 arranged at the bottom end of the teeth 7. The guides 2.7 taper towards the rotational axis A, so that the tabs 7.9 are held in the innermost position of the teeth 7 essentially play-free and form a defined rotational point for the teeth 7. The circular arc-shaped outwards and inwards movements of the teeth 7 are enabled by the expansion of the guides 7.7 outwards.

10

The external gear wheel 5 is embodied rotationally fixed or integrally with the second flange part 3. In the representations of Figures 2 and 7, the external gear wheel 5 and the eccentric ring 6 are drawn overlapping. The external gearing region 5.2 of the external gear wheel 5 with teeth 5.3 and recesses 5.4 (tooth gaps) formed in-between is used as a control surface. The number of tooth gaps 5.4 of the external gearing 5 can be, e.g., higher by one than the number of teeth 7 and the number of teeth 7 in turn can be equal to the number of webs 12.3 and less by one than the number of teeth 3.3 of the internal gearing 3.2 of the second flange part 3. The inner contact surfaces 7.4 of the teeth 7 come in contact with side faces of the teeth 5.3 of the external gear wheel 5 near their radially inner position, i.e., at the bottom teeth of Figure 2 or the teeth 7 shown in Figure 7.

Through the positive-fit holding of the inner contact surfaces 7.4 of the teeth 7 on the external gear wheel 5, a defined rotation of the teeth 7 at its innermost position corresponding to a bottom dead center is achieved; alternatively, a frictional-connection contact of the teeth 7 on a control disk fixed rotationally,

25

e.g., to the input shaft 4, is also possible. This results in a continuous support of the teeth 7 on the eccentric ring 6, which acts as a drive element and through which a functional separation of the driving effect and the control surface creating the rotation or tipping of the teeth is achieved.

5

According to the embodiment of Figure 12, the second part 20 is formed integrally with the camshaft and the first part 30 is formed integrally with the camshaft wheel 30.

10 For the embodiment shown in Figure 18 [sic: 13], essential parts correspond to those of the first embodiment and therefore are not described in more detail. The adjusting device has teeth 27 with lateral shoulder regions 27.1 and webs 22.3 with lateral shoulder regions 22.4, which come into contact with each other in the gliding movement of the teeth 27. Through the shaping with the
15 shoulder regions, the movement of the teeth can be defined sufficiently, so that in contrast with the embodiment of Figures 1 to 11, the slot-peg guide can be eliminated. Thus, the entire guide and force transfer occurs in a plane, e.g., tipping moments acting on the teeth out of the plane can be prevented. Also for this embodiment, an external gear wheel 15 is provided as a control gear
20 wheel. This external gear wheel engages the bottom regions of the teeth 27 with its external gearing 15.2.

According to the invention, the external gear wheel 5 or 15 can also be decoupled from the driven shaft and supported, e.g., so that it rotates freely.

25 For such an arrangement, the teeth 7 or 27 drive the freely rotating external gear wheel 5 for its inwards movement and are turned by the external gear wheel.

THIS PAGE BLANK (USPTO)

CLAIMS

1. Adjusting device for adjusting a camshaft (20) relative to a camshaft gear wheel (30) driven by a crankshaft, wherein parts (2, 3) provided for the adjusting procedure are each arranged on the camshaft gear wheel (30) and on the camshaft (20), and the adjusting device further comprises
- 5 an input shaft (4),
an eccentric drive element (4.2, 6) that can be driven by the input shaft,
a first part (2) with webs (2.3, 22.3), which are spaced apart in a peripheral direction and between which chambers (2.4) are formed,
10 a second part (3) with internal gearing (3.2, 13.2), and
several teeth (7, 27), which are arranged in the chambers (2.4) spaced apart from each other in the peripheral direction, each having an inner contact surface (7.4) for contact with a drive element (6) and an outer contact surface (7.5) for engagement in the internal gearing (3.2, 13.2) and which are adjustable in a radial direction when the input shaft (4) rotates,
- 15 wherein when the input shaft (4) rotates, the parts (2, 3) can rotate relative to each other in a self-locking way under engagement of the teeth (7, 27) in the webs (22.3) and in the internal gearing (3.2),
characterized in that
20 when the input shaft (4) rotates, the teeth (7, 27) in the chambers (2.4) can execute rotational movements about rotational axes parallel to a rotational axis (A) of the parts (2, 3).
2. Adjusting device according to Claim 1, characterized in that when the input shaft (4) rotates, each of the teeth (7, 27) can be guided on a first circular-arc path radially inwardly and then on a second circular-arc path radially outwardly.
- 25

3. Adjusting device according to Claim 1 or 2, characterized in that a control surface (5.2) is provided for engagement in the teeth (7, 27), wherein torque can be exerted on the teeth (7) by the control surface (5.2) for executing the rotational movements.

4. Adjusting device according to Claim 3, characterized in that the teeth (7, 27) are supported radially inwardly by the drive element (6) and the control surface (5.2) is led into engagement with an inner contact surface (7.4) of one of the teeth (7, 27) only in radially inner positions of the tooth (7, 27).

5. Adjusting device according to Claim 3 or 4, characterized in that the control surface is a control gearing region (5.2, 15.2) of a control gear wheel (5, 15), preferably an external gear wheel.

6. Adjusting device according to Claim 5, characterized in that the control gearing region is an external gearing region (5.2, 15.2) of an external gear wheel (5, 15) rotationally fixed to the second part (13).

7. Adjusting device according to Claim 5, characterized in that the control gear wheel (5, 15) is supported so that it can rotate freely about the rotational axis (A) of the parts.

8. Adjusting device according to one of Claims 3 to 5, characterized in that an axially projecting tab (7.9), which is held in a guide (2.7) of the first part (2), is formed on the tooth (7, 27).

9. Adjusting device according to Claim 8, characterized in that the guide is a recess (2.7) formed in the first part (2) between the webs (22.3).

10. Adjusting device according to Claim 8 or 9, characterized in that the guide
5 (2.7) tapers towards the rotational axis.

11. Adjusting device according to Claim 10, characterized in that the tooth (7, 27) can rotate in a radially inner position about a rotational axis defined by the tab (7.9).

10

12. Adjusting device according to one of Claims 1 to 5, characterized in that on side surfaces of the teeth and the webs acting as sliding surfaces, the teeth (27) and the webs (22) have shoulder regions (22.4, 27.1), which are led into contact with each other.

15

13. Adjusting device according to one of the preceding claims, characterized in that the webs (2.3, 22.3) taper towards the rotational axis.

14. Adjusting device according to one of Claims 1 to 3, characterized in that
20 the control surface (15.2, 5.2) is formed on a control disk (5, 15), which can rotate by means of the input shaft (4), preferably with a frictional connection between the control surface (5.2, 15.2) and the radially inner contact surfaces (7.4) of the teeth in radially inner positions thereof.

25 15. Adjusting device according to Claim 14, characterized in that the control disk (5) is led into engagement with the inner contact surfaces (7.4) of the teeth (7, 27) only in the control surface (5.2).

16. Adjusting device according to Claim 14 or 15, characterized in that the control disk (6) is fixed rigidly on the drive shaft (4), preferably by a locking tab of the drive shaft (4), which is guided by a locking recess of the control disk (5).

17. Adjusting device according to one of the preceding claims, characterized in that the webs (2.3, 22.3) have in a radially center region (2.6) a taper with concave side surfaces (2.5).

10

18. Adjusting device according to one of the preceding claims, characterized in that the teeth (7, 27) each have a center region (7.6) connecting the regions (7.2, 7.3) to at least partially concave side surfaces (7.7) between a radially inner region (7.2), which has the inner contact surface (7.4), and a radially outer region (7.3), which has the outer contact surface (7.5), for sliding and/or rolling contact on the webs (2.4).

15

19. Adjusting device according to one of the preceding claims, characterized in that the drive element is an eccentric ring (6), which is guided in a sliding manner on an eccentric disk (4.2) of the drive shaft (4).

20

20. Adjusting device according to Claim 19, characterized in that the eccentric ring (6) executes a wobble movement, preferably essentially without rotation, wherein the inner contact surfaces of the teeth (7, 27) roll on the eccentric ring (6).

25

21. Adjusting device according to one of the preceding claims, characterized in that the teeth (7, 17, 27) are biased in the radial direction.
22. Adjusting device according to Claim 21, characterized in that the teeth (7, 17, 27) are biased towards the rotational axis and have axially extending projections (7,1, 17.1) or regions, around which is set an elastic ring (8, 18) biased towards the rotational axis.
23. Adjusting device according to Claim 21, characterized in that the teeth (7, 17, 27) are biased radially outwardly and between an eccentric disk (4.2, 14.2) and the input shaft (4, 14) there is a biasing spring element (4.3), which presses the eccentric disk (4.2, 14.2) radially outwardly away from the input shaft (4, 14).
24. Adjusting device according to Claim 23, characterized in that the biasing spring element (4.3) is mounted through at least partial plastic deformation between the input shaft (4), preferably a flattened region (4.1) of the input shaft (4), and the eccentric disk (4.2, 14.2).

ABSTRACT

The invention relates to an adjusting device for adjusting two parts (2,3) with respect to one another that is used as a cam shaft adjuster. The objective of the invention is, with an easy and smooth operability, to ensure a self-locking and an at least extensive play-free, continuous adjustment of the two parts with a high degree of efficiency. To this end, the adjusting device comprises a first part (2) with webs (2.3, 22.3), which are interspaced in the peripheral direction and between which chambers (2.4) are formed, and includes a second part (3) with an internal gearing (3.2, 13.2), and a number of teeth (7, 27) that are arranged inside the chambers (2.4) while being interspaced in the peripheral direction. The adjusting device also includes an inner contact surface (7.4) for resting against an eccentric drive element (6), and includes an outer contact surface (7.5) for engaging inside the internal gearing (3.2, 13.2). When an input shaft (4) is rotated by the teeth (7, 27) located inside the chambers (2.4), rotational motions about rotation axes, which are parallel to a rotation axis (A) of the parts (2,3) can be executed.